`nodes[0]`, which is the index page of the site. It connects to `nodes[1]`, the about page, and indicates that 25 people navigated from the home page to the about page. That defines our flow—the flow of traffic through a site.

The Sankey layout is initialized like any layout:

```
var sankey = d3.sankey()
    .nodeWidth(20)
    .nodePadding(200)
    .size([460, 460])
    .nodes(data.nodes)
    .links(data.links)
    .layout(200);
```

Where to start and stop drawing the flows between nodes

The distance between nodes vertically; a lower value creates longer bars representing our web pages

The number of times to run the layout to optimize placement of flows

Until now, you've only seen `.size()`. It controls the graphical extent that the layout uses. The rest you'd need to figure out by looking at the example, experimenting with different values, or reading the sankey.js code itself. Most of it will quickly make sense, especially if you're familiar with the `.nodes()` and `.links()` convention used in D3 network visualizations. The `.layout()` setting is pretty hard to understand without diving into the code, but I'll explain that next.

After we define our Sankey layout as in listing 5.7, we need to draw the chart by selecting and binding the necessary SVG elements. In this case, that typically consists of `<rect>` elements for the nodes and `<path>` elements for the flows. We'll also add `<text>` elements to label the nodes.

Listing 5.7 Sankey drawing code

```
   var intensityRamp = d3.scale.linear()
     .domain([0,d3.max(data.links, function(d) {
                      return d.value;
}) ])
.range(["black", "red"]);

 d3.select("svg").append("g")
    .attr("transform", "translate(20,20)").attr("id", "sankeyG");

 d3.select("#sankeyG").selectAll(".link")
     .data(data.links)
     .enter().append("path")
     .attr("class", "link")
     .attr("d", sankey.link())
     .style("stroke-width", function(d) { return d.dy; })
     .style("stroke-opacity", .5)
     .style("fill", "none")
     .style("stroke", function(d){ return intensityRamp(d.value); })
     .sort(function(a, b) { return b.dy - a.dy; })
     .on("mouseover", function() {
               d3.select(this).style("stroke-opacity", .8);
     })
     .on("mouseout", function() {
     d3.selectAll("path.link").style("stroke-opacity", .5)
});
```

Offsets the parent <g> of the entire chart

Sankey layout's .link() function is a path generator

Note that layout expects us to use a thick stroke and not a filled area.

Sets the stroke color using our intensity ramp, black to red indicating weak to strong

Emphasizes the link when we mouse over it by making it less transparent