```
    var influentialLinks = originalLinks.filter(function (d) {
            return influentialNodes.indexOf(d.source) > -1 &&
                   influentialNodes.indexOf(d.target) > -1;
    });

    d3.selectAll("g.node")
        .data(influentialNodes, function (d) {return d.id})
        .exit()
        .transition()
        .duration(4000)
        .style("opacity", 0)
        .remove();

    d3.selectAll("line.link")
    .data(influentialLinks, function (d) {
                   return d.source.id + "-" + d.target.id;
    })
    .exit()
    .transition()
    .duration(3000)
    .style("opacity", 0)
    .remove();

    force
       .nodes(influentialNodes)
       .links(influentialLinks);

    force.start();
};
```

Makes an array of links only out of those that reference existing nodes

By setting a transition on the .exit(), it applies the transition only to those nodes being removed and waits until the transition is finished to remove them

Because the force algorithm is restarted after the filtering, you can see how the shape of the network changes with the removal of so many nodes. That animation is important because it reveals structural changes in the network.

Putting more nodes and edges into the network is easy, as long as you properly format your data. You stop the force layout, add the properly formatted nodes or edges to the respective arrays, and rebind the data as you've done in the past. If, for instance, we want to add an edge between Sam and Al as shown in figure 6.19, we need to stop the force layout like we did earlier, create a new datapoint for that edge, and add it to the array we're using for the links. Then we rebind the data and append a new line element for that edge before we restart the force layout.

Listing 6.10 A function for adding edges

```
function addEdge() {
    force.stop();
    var oldEdges = force.links();
    var nodes = force.nodes();
    newEdge = {source: nodes[0], target: nodes[8], weight: 5};
    oldEdges.push(newEdge);
    force.links(oldEdges);
    d3.select("svg").selectAll("line.link")
    .data(oldEdges, function(d) {
                return d.source.id + "-" + d.target.id;
    })
```