8.1.1 CSS

You use more CSS when you work with traditional DOM elements, because if you want to manipulate them in the way you manipulate SVG elements, you typically need to set them up a bit differently; for instance, if you want to place HTML elements precisely like you do with SVG elements. Also, most of the graphical aspects of these elements aren't set with attributes like in SVG, but with styles (we covered the difference between styles, attributes, and properties back in chapter 1). This shouldn't be a surprise for anyone who's had experience working with CSS, because it's usually the case in the complex examples and under the hood when you use JavaScript libraries. For example, if you look at the CSS of various libraries that provide autocomplete or more sophisticated UI elements, you'll see that they typically combine JavaScript with a variety of styles assigned to complex CSS selectors. In the following listing you'll see the style sheet we'll use for this chapter. Some of these elements, like `<img.infinite>`, you won't see until the end of the chapter.

Listing 8.1 Style sheet for chapter 8

```
tr {
  border: 1px gray solid;
}

td {
  border: 2px black solid;
}

div.table {
  position:relative;
}
div.data {
  position: absolute;
  width: 90px;
  padding: 0 5px;
}

div.head {
  position: absolute;
}

div.datarow {
  position: absolute;
  width: 100%;
  border-top: 2px black solid;
  background: white;
  height: 35px;
  overflow: hidden;
}

div.gallery {
  position: relative;
}

img.infinite {
  position: absolute;
```