```
var function1 = d3.selectAll("div");
var function1withData = function1.data(someData);
var function2 = function1withData.enter();
var function3 = function2.append("div");
function3.html("Wow");
var function4 = function3.append("span");
function4.html("Even More Wow");
function4.style("font-weight", "900");
```

You can see this when you run the code in your console. This is the first time you've used the `.data()` function, which along with `.select()` is at the core of developing with D3. When you use `.data()`, you bind each element in your selection to each item in an array. If you have more items in your array than elements in your selection, then you can use the `.enter()` function to define what to do with each extra element. In the previous function, you select all the `<div>` elements in the `<body>` and the `.enter()` function tells D3 to `.append()` a new div when there are more elements in the array than elements in the selection. Given that your d3ia.html page already has one div, if you bind an array with more than one value, D3 appends, or adds, a div for each value in the array beyond the first.

A corresponding `.exit()` function defines how to respond when an array has fewer values than a selection. For now, you'll run the code as it appears in the examples, and in later chapters we'll get into much more detail on the way selections and binding work.

With this example, you're not doing anything with the data in the array and only creating elements based on the size of the array (one `<div>` for each element in the array). This example assumes that you already have a `<div>` in your html with a black border (as seen in figure 1.25). Here's the HTML that would get that done:

```
<!doctype html>
<html>
<script src="d3.v3.min.js" type="text/JavaScript"></script>
<style>
#borderdiv {
width: 200px;
height: 50px;
border: 1px solid gray;
}
</style>
<body>
  <div id="borderdiv"></div>
  </body>
</html>
```

For this to work, you need to give `someData` a value. With that in place, you can run your code:

```
var someData = ["filler", "filler", "filler", "filler"];
d3.select("body").selectAll("div")
  .data(someData)
  .enter()
  .append("div")
  .html("Wow")
```