```
"Naples",1000000,"Italy",14,40
"Rio",12300000,"Brazil",-43,-22
"Sao Paolo",12300000,"Brazil",-46,-23
```

Listing 2.2 File contents of tweets.json

```
{
"tweets": [
{"user": "Al", "content": "I really love seafood.",
   "timestamp": " Mon Dec 23 2013 21:30 GMT-0800 (PST)",
   "retweets": ["Raj","Pris","Roy"], "favorites": ["Sam"]},
{"user": "Al", "content": "I take that back, this doesn't taste so good.",
   "timestamp": "Mon Dec 23 2013 21:55 GMT-0800 (PST)",
   "retweets": ["Roy"], "favorites": []},
{"user": "Al",
   "content": "From now on, I'm only eating cheese sandwiches.",
   "timestamp": "Mon Dec 23 2013 22:22 GMT-0800 (PST)",
   "retweets": [],"favorites": ["Roy","Sam"]},
{"user": "Roy", "content": "Great workout!",
   "timestamp": " Mon Dec 23 2013 7:20 GMT-0800 (PST)",
   "retweets": [],"favorites": []},
{"user": "Roy", "content": "Spectacular oatmeal!",
   "timestamp": " Mon Dec 23 2013 7:23 GMT-0800 (PST)",
   "retweets: [],"favorites": []},
{"user": "Roy", "content": "Amazing traffic!",
   "timestamp": " Mon Dec 23 2013 7:47  GMT-0800 (PST)",
   "retweets": [],"favorites": []},
{"user": "Roy", "content": "Just got a ticket for texting and driving!",
   "timestamp": " Mon Dec 23 2013 8:05 GMT-0800 (PST)",
   "retweets": [],"favorites": ["Sam", "Sally", "Pris"]},
{"user": "Pris", "content": "Going to have some boiled eggs.",
   "timestamp": " Mon Dec 23 2013 18:23 GMT-0800 (PST)",
   "retweets": [],"favorites": ["Sally"]},
{"user": "Pris", "content": "Maybe practice some gymnastics.",
   "timestamp": " Mon Dec 23 2013 19:47  GMT-0800 (PST)",
   "retweets": [],"favorites": ["Sally"]},
{"user": "Sam", "content": "@Roy Let's get lunch",
   "timestamp": " Mon Dec 23 2013 11:05 GMT-0800 (PST)",
   "retweets": ["Pris"], "favorites": ["Sally", "Pris"]}
]
}
```

With these two files, we can access the data by using the appropriate function to load them:

```
d3.csv("cities.csv",function(data) {console.log(data)});
d3.json("tweets.json",function(data) {console.log(data)});
```

Prints "Object {tweets: Array[10]}" in the console

In both cases, the data file is loaded as an array of JSON objects. For tweets.json, this array is found at `data.tweets`, whereas for cities.csv, this array is `data`. The function `d3.json()` allows you to load a JSON-formatted file, which can have objects and attributes in a way that a loaded CSV can't. When you load a CSV, it returns an array of objects, which in this case is initialized as `data`. When you load a JSON file, it could