```
circle {
fill: pink;
stroke: black;
stroke-width: 1px;
}

circle.active {
fill: red;
}

circle.inactive {
fill: gray;
}
```

3.1.5 External libraries

For the example in this chapter, we'll use two more .js files besides d3.min.js, which is the minified D3 library. The first is soccerviz.js, which stores the functions we'll build and use in this chapter. The second is colorbrewer.js, which also comes bundled with D3 and provides a set of predefined color palettes that we'll find useful.

We reference these files in the much cleaner d3ia_2.html.

Listing 3.2 d3ia_2.html

```
<html>
<head>
  <title>D3 in Action Examples</title>
  <meta charset="utf-8" />
  <link type="text/css" rel="stylesheet" href="d3ia.css" />
</head>
<script src="d3.v3.min.js" type="text/javascript"></script>
<script src="colorbrewer.js" type="text/javascript"></script>
<script src="soccerviz.js" type="text/javascript"></script>
<body onload="createSoccerViz()">
<div id="viz">
<svg style="width:500px;height:500px;border:1px lightgray solid;" />
</div>
<div id="controls" />
</body>
</html>
```

The <body> has two elements, one with the ID viz and the other with the ID controls. Notice that the <body> element has an onload property that runs createSoccerViz(), one of our functions in soccerviz.js (shown in the following listing). This loads the data and binds it to create a labeled circle for each team. It's not much, as you can see in figure 3.2, but it's a start.

Listing 3.3 soccerviz.js

```
function createSoccerViz() {
  d3.csv("worldcup.csv", function(data) {
    overallTeamViz(data);
  })
```

Loads the data and runs createSoccerViz with the loaded data