This chapter focuses on step 2 of this process. We will define data product boundaries and then apply ownership.

In chapter 3, we described a simplified way of finding data product boundaries, using the simple business processes and datasets involved. In this chapter, we will give you more tools for your toolbox so that you can find boundaries that better reflect the business and that will be easier to maintain by development teams. Although this chapter provides improvements, the high-level process of building a data mesh generally stays the same as described in chapter 3.

We start the process of finding boundaries by explaining how to understand, capture, and visualize our domain and define *domain* and *domain-driven design*. We will use the domain storytelling technique (section 4.1).

Following that, we will teach you how to decompose your domain by using business capability modeling. We also will explain how those techniques will help you find the boundaries of data products. With the boundaries discovered, we will show you how to use domain decomposition to implement team ownership. We will supplement the learning process of these practical skills with the introduction of the subdomain, business capability, and data domain concepts (section 4.2).

Next, we will show you an alternative way of finding data product boundaries, using data use cases. In the end, you will be able to apply team ownership to data products (section 4.3).

After that, we will explore the concept of heuristics and how to use it to find even more possible boundaries of data products. We will show you multiple heuristics. After reading this chapter, you will know how to apply them in practice (section 4.4).

Finally, we will take a step back to look at the data mesh from the perspective of multiple interconnected domain-oriented data products (section 4.5).

All those steps form a process, illustrated in figure 4.1.