- *Simple files*—For example, results of a series of measurements taken on geological samples, Excel reports, or data in CSV format exported from the application. In this case, a description in the form of metadata can also be crucial for further use of the files.
- *A dataset inside a database (or data storage in general)*—Containing a read-optimized representation of data from a source system (system of records).
- *A dataset built based on data retrieved from a COTS-type system (commercial, off the shelf)*—For example, containing information about stock levels.
- *REST API*—Data exposed from applications to read transactional data, optimized for reading, optionally supporting Hypermedia as the Engine of Application State (HATEOAS) to facilitate automated (machine-consumable) data consumption.
- *Data stream representing the history of changes to the application*—For example, events that relate to changes made within a billing account.
- *Data stream representing snapshots of data entities from a transaction system*—For example, information about a system user.
- *Data mart*—Representing data enabling multidimensional analysis of sales results.
- *Denormalized table*—Containing search-optimized information (for example, about the rentals of a particular movie).
- *Graph database*—Reflecting complex relationships between data (for example, specialized for finding movie recommendations).
- *Local data lake or part of a bigger data lake*—Used to build a view used as a basis for analysis of watching movies statistics.
- *MDM-type database (master data management)*—Containing an integrated view on system users (personal information, viewing preferences, viewing time preferences, payment information, rating information, etc.).

As you can see from the examples, there are many possibilities. But of course, these are just examples of the data itself, the core of a data product. A data mesh does not dictate a particular form of data representation or a specific technology.