1. (Meta)data is retrievable by its identifier using a standardized communications protocol:
    - The protocol is open, free, and universally implementable.
    - The protocol allows for an authentication and authorization procedure, where necessary.
2. Metadata is accessible, even when the data is no longer available.

As shown in the previous section, the data product has an ID in the form of the URL https://dp.meshflix.com/93384349834. According to principle 1, this should be a workable URL that can be used to retrieve information about the data product. For example, entering this URL into a browser should produce the final metadata file in the response. In this case, Hypertext Transfer Protocol (HTTP) is used, which supports authentication and authorization, so the whole principle 1 is fulfilled. Principle 2 says that this metadata link should be working, even when the data product is no longer available.

These accessibility principles can be seen as recommendations for creating a data product and its desirable features to facilitate its use. In particular, the permanent availability of metadata is essential if there is a need to refer to historical data (e.g., for legal reasons). Hence, at the implementation level, a registry of data product metadata that allows retrieving the data for any identifier can be helpful. Furthermore, standard protocols and formats should be chosen when creating infrastructure and platforms (e.g., HTTPS/JSON).

5.6.3 Interoperable

According to FAIR, data should be easy to integrate with other data, and therefore should be defined so that data in other data products, vocabularies, and ontologies can be referenced. In this case, FAIR proposes three principles:

1. (Meta)data uses a formal, accessible, shared, and broadly applicable language for knowledge representation.
2. (Meta)data uses vocabularies that follow FAIR principles.
3. (Meta)data includes qualified references to other (meta)data.