To make data interpretable by others, we have to describe the data model. We should use a well-recognized language, such as Resource Description Framework (RDF), OWL, JSON-LD, or Schema.org (principle 1). Also, we should use vocabularies that follow FAIR rules (principle 2). Listing 5.5 includes a reference to an enum defining a `gender` property:

```
{
        "name": "gender",
        "uri": "https://ref.meshflix.com/generic/123393ed34",
        "titles": "Gender",
        "datatype": "enum"
}
```

This is also an example for principle 3, as we refer to external definitions in the form of a fully qualified reference ("uri": "https://ref.meshflix.com/generic/123393ed34"). Beware that in the provided example the custom-created `gender` enum is used, but we could also use `https://schema.org/gender` alternatively for the same purpose.

If we want to go beyond a single data product to perform more complex analyses, we must have the appropriate means to do so. The previous FAIR principles are quite demanding because they significantly expand the amount of information that needs to be provided with metadata and data. Still, they are the only way we can get the advantage of using data by linking it. For example, relationships are not defined in external tools but are part of the data product description: its metadata. Thus, from a pragmatic perspective, these principles can be treated as recommendations when creating a data product and defining its maturity levels.

5.6.4 Reusable

The last point of FAIR focuses on data reusability, or the ability to apply the same data in different contexts. The principles associated with reusability are as follows: