```
import pyspark.pandas as ps

df = ps.read_table("oil_prices")
df.head(10)
```

▸ (2) Spark Jobs

	date	dcoilwtico
0	2015-05-04	58.92
1	2015-05-05	60.38
2	2015-05-06	60.93
3	2015-05-07	58.99
4	2015-05-08	59.41
5	2015-05-11	59.23
6	2015-05-12	60.72

Figure 4.22 – View the oil price data provided by Kaggle in the Favorita Sales dataset

If we add the `date` column as the index column, as shown in the notebook, you'll see that the rows are then in order. However, January 5th and January 6th are missing. This occurs because stock prices are not given for holidays or weekends.

```
df = (
    df.reindex(ps.date_range(df.index.min(), df.index.max()))
    .reset_index()
    .rename(columns={"index": "date"})
    .ffill()
)
df.to_table("oil_prices_silver")
df.head(10)
```

Figure 4.23 – Reindex to include all dates and fill forward missing prices

We use the `reindex()` command to create an updated index based on the minimum and maximum dates in the oil price data. The reindex creates rows for all missing dates. When new rows are created for the missing dates, the prices are NaNs. We use the `ffill()` function, or forward fill, to update the DataFrame by filling in dates without prices with the price from the day before. January 1st, 2013, doesn't have a previous day to fill from, so it remains `NaN`.

Now, we have a clean and consistent silver table of oil prices that we can pull into our Favorita time-series models. In the next chapter, we will do feature engineering with the Favorita sales data.