```
CREATE
OR REPLACE TABLE stores_ft AS(
  SELECT
    store_nbr,
    city,
    state,
    `type` as store_type,
    `cluster` as store_cluster
  FROM
    favorita_stores
  );
ALTER TABLE stores_ft ALTER COLUMN store_nbr SET NOT NULL;
ALTER TABLE stores_ft ADD PRIMARY KEY(store_nbr);
COMMENT ON TABLE stores_ft IS 'Favorita Store features include geography, store
cluster, and store_type.';
```

Figure 5.34 – Creating the stores_ft feature table from the favorita_stores table using SQL

Executing the code in *Figure 5.34* creates a feature table called `stores_ft` that we will use as a central repository for important store details. `store_nbr` is set to `NOT NULL` because it is the primary key. The table does not contain a date column, so this feature table is not a time series feature table. If it did, we could include an additional `TIMESERIES` primary key. Note that when adding the primary key to the table, you can name the constraint for the primary key with a unique name, as shown in the documentation. We prefer to let the DFE client name the constraint automatically. You can use `DESCRIBE TABLE EXTENDED` to see the name of your primary key constraint.

The remaining two feature tables are time series tables. After some transformations, we will create the feature tables using Python and the DFE client. Let's focus on the holidays first.

date	type	locale	locale_name	description	transferred
2012-03-02 00:00:00.000	Holiday	Local	Manta	Fundacion de Manta	false
2012-04-01 00:00:00.000	Holiday	Regional	Cotopaxi	Provincializacion de Cotopaxi	false
2012-04-12 00:00:00.000	Holiday	Local	Cuenca	Fundacion de Cuenca	false
2012-04-14 00:00:00.000	Holiday	Local	Libertad	Cantonizacion de Libertad	false
2012-04-21 00:00:00.000	Holiday	Local	Riobamba	Cantonizacion de Riobamba	false

Figure 5.35 – The holiday events table

The features we create are their respective store's local, regional, and national holidays. We can look at *Figure 5.35* to recall what the holiday data looked like.

One thing to note about our data is that there are days when multiple holidays occur for the same store. We process the three types of holidays very similarly. The transformations for national holidays are slightly different, given that there is no need to match on locale. All holiday transformations are present in the GitHub code. However, we do not cover each in detail in the book.