2. After completing the same process in the previous steps for regional and national holidays, we combine the silver tables into a single DataFrame. We use full joins to include all holidays. To avoid `null` dates and store numbers, we chain two `ifnull()` functions:

```
df = sql("""
    SELECT
      ifnull(n.`date`,ifnull(r.`date`, l.`date`)) as `date`,
      ifnull(n.store_nbr,ifnull(r.store_nbr, l.store_nbr)) as store_nbr,
      n.national_holiday_type,
      r.regional_holiday_type,
      l.local_holiday_type
    FROM
      national_holidays_silver n
    FULL JOIN regional_holidays_silver r ON n.`date`=r.`date` AND n.store_nbr = r.store_nbr
    FULL JOIN local_holidays_silver l ON n.`date`=l.`date` AND n.store_nbr = l.store_nbr
    ORDER BY
      `date`
    """)
```

Figure 5.39 – Combining all three silver tables into a single DataFrame

3. Now that we have prepared our DataFrame with the features we want to save, we use the DFE `create_table` method to save the DataFrame as a feature table. We specify `primary_keys`. Be sure to note that we are *not* including a time series column. This is because we want the feature table lookup only to match exact dates. Holidays would not function well with the point-in-time logic. The primary keys will also be our lookup keys when we create the training set in the next chapter. A best practice is to include a thoughtful description as well.

```
fe.create_table(
    name = f"store_holidays_ft",
    primary_keys=["date", "store_nbr"],
    df=df,
    description="Holidays in Ecuador by date and store number. Table includes
    holiday types for national, regional, and local. Days where a store has more
    than one holiday is indicated by holiday type being 'Multiple'. Nulls indicate
    non-holiday days.",
)
```

Figure 5.40 – Creating the store holidays feature table using the DFE client

4. Notice that in our feature table, *Figure 5.41*, there are `null` values when there is not a holiday of a specific holiday of such type. When we create the training set, the feature lookup functionality will have `null` for the values of dates not in the table. We do not need to create `null` rows for each date that is not a holiday, thus saving us the preprocessing time.