Chapter 8, *Monitoring, Evaluating, and More*, covers how to create visualizations for dashboards in both the new Lakeview dashboards and the standard DBSQL dashboards. Deployed models can be shared via a web application. Therefore, we will not only introduce Hugging Face Spaces but also deploy the RAG chatbot using a Gradio app to apply what we have learned.

To get the most out of this book

Software/hardware covered in the book	Operating system requirements
Databricks	Windows, macOS, or Linux
Python and its associated libraries	Windows, macOS, or Linux

If you are using the digital version of this book, we advise you to type the code yourself or access the code from the book's GitHub repository (a link is available in the next section). Doing so will help you avoid any potential errors related to the copying and pasting of code.

This book contains a few long screenshots which have been captured to show the overview of workflows and also the UI. Due to this, the content in this images may appear small at 100% zoom. Please check out the PDF copy provided with the book to zoom in for clearer images.

Download the example code files

You can download the example code files for this book from GitHub at `https://github.com/PacktPublishing/Databricks-ML-In-Action`. If there's an update to the code, it will be updated in the GitHub repository.

We also have other code bundles from our rich catalog of books and videos available at `https://github.com/PacktPublishing/`. Check them out!

Conventions used

There are a number of text conventions used throughout this book.

`Code in text`: Indicates code words in text, database table names, folder names, filenames, file extensions, pathnames, dummy URLs, user input, and Twitter handles. Here is an example: " For example, you could select the `ml_in_action.favorita_forecasting.train_set` table."

A block of code is set as follow:

```
import opendatasets as od

od.download("https://www.kaggle.com/competitions/store-sales-time-
series-forecasting/data",raw_data_path)

dbutils.fs.ls(raw_data_path + "/store-sales-time-series-forecasting/")
```