```
import os
import mlflow
from mlflow.store.artifact.models_artifact_repo import ModelsArtifactRepository
from mlia_utils.cv_clf_funcs import select_best_model

experiment_path = f"/Users/{current_user}/intel-clf-training_action"
local_path = select_best_model(experiment_path)

requirements_path = os.path.join(local_path, "requirements.txt")
if not os.path.exists(requirements_path):
  dbutils.fs.put("file:" + requirements_path, "", True)

device = "cuda" if torch.cuda.is_available() else "cpu"
loaded_model = torch.load(local_path+"/data/model.pth", map_location=torch.device
(device))
loaded_model
```

Figure 6.31 – Defining experiment, requirements, and loading our model into GPU

Figure 6.32 runs simple example to confirm that our model performs well. We have again minimized some of the code for improved readability, but you can find the full code in the notebook.

```
  import matplotlib.pyplot as plt
  from torch.autograd import Variable
  from mlia_utils import cv_clf_funcs as cv_funcs

  transform_tests = cv_funcs.transform_imgs()

> def pred_class(img):…

  classes = {k:v for k , v in enumerate(sorted(outcomes))}
  loaded_model.eval()

  plt.figure(figsize=(20,20))
> for i, images in enumerate(pred_files[:50]):…
```

Figure 6.32 – Simple example to verify model predictability