```
if model_details.description == "":
  print("No model description found. Please add a model description to pass this test.")
  validation_results['description'] = 0
elif len(model_details.description) < 15:
  print("Model description is too short. Perhaps include a note about the business impact.")
  validation_results['description'] = 0
else:
  validation_results['description'] = 1
```

Figure 7.20 – Validating a model description is present

Similar to *Figure 7.20*, the notebook checks for tags. These are examples to get you started. This is an ideal section to expand on the current code; and continue adding validation results and update tags, *Figure 7.21*.

```
  if sum(validation_results.values()) == len(validation_results.values()):
    mlfclient.set_model_version_tag(name=model_name, key="validation_status", value="passed_tests",
    version=model_version)
    print(f"Success! Your model, {model_name} version {model_version}, passed all tests.")
  else:
    mlfclient.set_model_version_tag(name=model_name, key="validation_status", value="failed_tests",
    version=model_version)
    print(f"Fail! Check the results to determine which test(s) the model failed. {validation_results}")
```

```
Success! Your model, ml_in_prod.synthetic_transactions.packaged_transaction_model version 8, passed all tests.
```

Figure 7.21 – Processing the results of the validation tests

With a tested model, you can progress to inference; see the `CH7-08-Batch Inference` notebook. Review the examples of performing batch inference on a DataFrame (*Figure 7.22*) and a JSON data string.

```
from databricks.feature_engineering import FeatureEngineeringClient
from mlia_utils.mlflow_funcs import get_latest_model_version
import mlflow
mlflow.set_registry_uri("databricks-uc")
fe = FeatureEngineeringClient()

scoring_df = sql("SELECT * FROM raw_transactions ORDER BY TransactionTimestamp DESC").drop("Label").limit(100)

print(f"Scoring model={model_name} version={get_latest_model_version(model_name)}")

scored = fe.score_batch(
  model_uri=f"models:/{model_name}/{get_latest_model_version(model_name)}",
  df=scoring_df,
  env_manager="conda"
)

display(scored)
```

Figure 7.22 – Load and score the model in batch on a DataFrame