Next, we create our model serving endpoint using the Databricks SDK. You could also create your endpoint using the UI. If you decide to use SDK, you must create a configuration file for your endpoint. The example below is for a CPU container with a small workload size. If you are unfamiliar with this option, please check out *Create model serving endpoints* in the *Further reading* section.

```
import mlflow
from mlia_utils.mlflow_funcs import *

# Create or update serving endpoint
from databricks.sdk import WorkspaceClient
from databricks.sdk.service.serving import EndpointCoreConfigInput, ServedModelInput

serving_endpoint_name = "cvops_model_mlaction_endpoint"
latest_model_version = get_latest_model_version(model_name)


w = WorkspaceClient(host=db_host, token = db_token)

endpoint_config = EndpointCoreConfigInput(
    name=serving_endpoint_name,
    served_models=[
        ServedModelInput(
            model_name=model_name,
            model_version=latest_model_version,
            workload_size="Small",
            scale_to_zero_enabled=True
        )
    ]
)
```

Figure 7.36 – Setting config input for the endpoint to serve our model

Once the settings are provided, you are ready to deploy or to update your endpoint in the event that it already exists.

```
import os
serving_endpoint_url = f"{db_host}/ml/endpoints/{serving_endpoint_name}"

try:
  w.serving_endpoints.get(serving_endpoint_name)
  print(f"Updating the endpoint {serving_endpoint_url} to version {latest_model_version}, this will take a few minutes to package and
  deploy the endpoint...")
  w.serving_endpoints.update_config_and_wait(served_models=endpoint_config.served_models, name=serving_endpoint_name)
except:
  print(f"Creating the endpoint {serving_endpoint_url}, this will take a few minutes to package and deploy the endpoint...")
  w.serving_endpoints.create_and_wait(name=serving_endpoint_name, config=endpoint_config)

displayHTML(f'Your Model Endpoint Serving is now available. Open the <a href="/ml/endpoints/{serving_endpoint_name}">Model Serving Endpoint
page</a> for more details.')
```

Your Model Endpoint Serving is now available. Open the Model Serving Endpoint page for more details.

Figure 7.37 – Deploying a new endpoint if does not exist or updating the existing one