```
--Create a SQL UDF
CREATE FUNCTION redact(a STRING)
RETURNS STRING
LANGUAGE PYTHON
AS $$
import json
keys = ["phone", "email"]
obj = json.loads(a)
for k in obj:
  if k in keys:
    obj[k] = "REDACTED"
return json.dumps(obj)
$$;

-- Grant execute so sales analysts can use the SQL UDF
GRANT EXECUTE ON sales.customer_db.redact TO sales-analysts

--Members of the sales-analyst group can use the redact UDF in their SQL expressions
-- Using the redact UDF to remove phone and email from the contact_info field
SELECT customer_id, redact(contact_info) FROM sales.customer_db.customer_data
```

Figure 8.8 – Creating a Python UDF in DBSQL

UDFs are defined and managed as part of Unity Catalog. Once a UDF is defined, you can give teams the ability to execute the UDF using `GRANT EXECUTE`.

```
--Create a SQL UDF
CREATE FUNCTION redact(a STRING)
RETURNS STRING
LANGUAGE PYTHON
AS $$
import json
keys = ["phone", "email"]
obj = json.loads(a)
for k in obj:
  if k in keys:
    obj[k] = "REDACTED"
return json.dumps(obj)
$$;

-- Grant execute so sales analysts can use the SQL UDF
GRANT EXECUTE ON sales.customer_db.redact TO sales-analysts

--Members of the sales-analyst group can use the redact UDF in their SQL expressions
-- Using the redact UDF to remove phone and email from the contact_info field
SELECT customer_id, redact(contact_info) FROM sales.customer_db.customer_data
```

Figure 8.9 – Granting permissions for the sales-analysts groups to execute a UDF