7. Create a secret for storing your Kaggle username:

```
/usr/local/bin/databricks secrets put-secret --json '{"scope":
"machine-learning-in-action",
"key": "kaggle_username",
"string_value": "readers-username"
}'
```

8. Create a secret for storing your Kaggle API key:

```
/usr/local/bin/databricks secrets put-secret --json '{
"scope": "machine-learning-in-action",
"key": "kaggle_key",
"string_value": "readers-api-key"
}'
```

9. Last, list your secrets to make sure everything works as expected:

```
/usr/local/bin/databricks secrets list-secrets "machine-
learning-in-action"
```

In *Chapter 8*, we'll create another scope to hold an OpenAI API key, but for now we just need the Kaggle credentials. Now that we have our secrets set up, let's get our codebase ready!

Setting up your code base

We use a setup file to help keep variables consistent across multiple project notebooks. You will run the setup file each time you run the project notebooks using a magic command, `%run`. This command brings everything into the memory of your notebook session. The `global-setup.py` file has numerous components to it. Let's walk through each section. Feel free to edit the file to fit your needs.

> **Note**
>
> It's possible you'll receive an error message: `py4j.security.Py4JSecurityException: Method public scala.collection.immutable.Map com.databricks.backend.common.rpc.CommandContext.tags() is not whitelisted on class class com.databricks.backend.common.rpc.CommandContext`
>
> This is because you are on a shared compute cluster. You can simply hardcode `current_user` to your username.