In the following code block (*Figure 2.19*), we use the Python package `opendatasets`, a library specifically created to download data from the Kaggle API. You can find more information in the *Further reading* section.

```
import opendatasets as od

od.download("https://www.kaggle.com/competitions/
store-sales-time-series-forecasting/data",raw_data_path)
```

Figure 2.19 – Downloading Favorita data from opendatasets

That is all for the *Favorita Store Sales* project in this chapter! Now, we can focus on generating data for our `Streaming Transactions` project.

Project: Streaming Transactions

Your goal with the Streaming Transactions project is to build a model to classify transactions. The dataset consists of JSON-formatted transactions with `Transaction`, `timestamp`, `Label`, `Amount`, and `CustomerID`.

In later chapters, you will add a product column to demonstrate schema evolution. In this chapter, you'll create the first version of transaction data used throughout the rest of the book. To follow along in your workspace, please open the following notebook:

- `CH2-01-Generating Records Using DBKS Labs Datagen`

You can run each cell of the notebook as we work through them or run them all at once. After the setup commands, we set notebook variables to establish the number of rows generated per batch of transactions (`nRows`), the number of positively labeled rows per batch (`nPositiveRows`), the path to the volume where you will store the JSON dataset (`destination_path`), a temporary path (`temp_path`), and the number of seconds between each batch of data you generate (`sleepIntervalSeconds`).

The following code block accesses the value of the `Reset` widget. Any data already written to the volume will be deleted if the widget is set to `True` (its default value).

```
if bool(dbutils.widgets.get('Reset')):
  dbutils.fs.rm(temp_path, recurse=True)
  dbutils.fs.rm(destination_path, recurse=True)
  dbutils.fs.mkdirs(destination_path)
```

Figure 2.20 – Checking the Reset widget