```
df = (
        spark.read.format("binaryfile")
        .option("recursiveFileLookup", "true")
        .load('dbfs:'+ documents_folder)
        )

df.write.mode("overwrite").saveAsTable(f"{catalog}.{database_name}.{table_name}")
```

Figure 3.20 – Read the PDF file in binary format and write it into a Bronze layer table

3. Let's see how it looks in a Delta table view. The binary format of each PDF is in the content column:

```
display(sql(f"SELECT * FROM {table_name} LIMIT 2"))
```

▸ (3) Spark Jobs

Table + New result table: ON Search

		modificationTime	length	content
1	f	2024-03-10T00:51:17.000+00:00	2119311	JVBERi0xLjUKJY8KMTc5IDAgb2JqCjw8IC9GaV
2	f	2024-03-10T00:51:18.000+00:00	1051746	JVBERi0xLjUKJY8KNjcgMCBvYmoKPDwgL0Zpl

Figure 3.21 – Displaying ingested PDF content into Delta Table

4. Next, we write a helper function using the `unstructured` library to extract the text from the PDF bytes. The function is in the `mlia_utils.rag_funcs` script.

```
from unstructured.partition.auto import partition
import re
import io

def extract_doc_text(x : bytes) -> str:
  # Read files and extract the values with unstructured
  sections = partition(file=io.BytesIO(x))
  def clean_section(txt):
    txt = re.sub(r'\n', '', txt)
    return re.sub(r' ?\.', '.', txt)
  # Default split is by section of document
  # concatenate them all together because we want to split by sentence instead.
  return "\n".join([clean_section(s.text) for s in sections])
```

Figure 3.22 – The helper function definition to extract document text