3.2.1. Browser events

A quick recap of the program you've been writing for Scruffy and Agtron's party is in order. So far you can count the number of guests attending the party by reading the attendee list from a file called partygoers.txt. Next, you need to create a website for the party that always shows the current attendee count. Scruffy started creating a site for the party, but he had to abandon the project at the last minute to tour Greenland as a xylophonist. Luckily, he had already started on it. You already have an HTML document:

```
<!doctype html>
<html>
<title>How many people are coming?</title>
<script src='attendees.js'></script>
<body>
<div id='how-many-attendees'>How many attendees?</div>
</body>
</html>
```

To get your CoffeeScript program to run in the browser when you load this document, you need to first compile it to a file called attendees.js.

The element that will hold the attendee count.

You want to replace the words *How many attendees?* with the current attendees count. Scruffy also left you some code that shows how to update the content:

```
document.querySelector('#how-many-attendees').innerHTML = 55
```

Update the content 'How many attendees?' with 55.

So, how do you update the content with the latest attendees? Forget about web browsers entirely for a minute and think about whether you've seen anything so far in CoffeeScript to do that. You haven't, but you're about to see something that gets you part of the way. It's called `setInterval`.

---

document.querySelector?

The `document.querySelector` method is part of the Document Object Model (DOM) API that you use to manipulate things in a web browser. You'll find more about browsers in chapter 11.

3.2.2. Using timeouts and intervals to create events