```
countWordsInFile = (fileName) ->
  stream = fs.createReadStream fileName
  stream.setEncoding 'ascii'
  wordCount = 0
  stream.on 'data', (data) ->
    lines = data.split /\n/gm
    wordCount = wordCount + countMany lines
  stream.on 'close', () ->
    console.log "#{wordCount} words"

file = process.argv[2]

if file
  countWordsInFile file
else
  console.log 'usage: coffee wordcount.coffee [file]'
```

Read the file in as a stream and perform a word count on each stream.

Get the filename from command-line argument.

Handle command line.

Where's reduce?

If you're thinking that the `countMany` function could have just reduced the array instead of iterating manually, you're correct. If you don't know what `reduce` is, then that's fine too; carry on.

3.4.3. Functions as arguments

Good news! You've already seen functions used as arguments. For example, the `setTimeout` method takes a function as an argument:

```
invokeLater = -> console.log 'Please invoke in one second'
setTimeout invokeLater, 1000
```

This has uses other than callback functions, though.

Summing an array

Just when you thought you had the party attendee count page covered, there's a problem. People are allowed to bring friends to the party, and those friends aren't being included in the attendee list. Instead, you're now getting emailed another *guests* file containing the number of friends each person is bringing. Like the attendee list, the guest list is too long to print here, but it's in this format: