```
oneMore()
# 1
```

Applied example

This same technique can be used to create a function that will always return the contents of the most recently modified of two files:

```
makeMostRecent = (file1, file2) ->
  mostRecent = 'Nothing read yet.'

  sourceFileWatcher = (fileName) ->
    sourceFileReader = ->
      fs.readFile fileName, 'utf-8', (error, data) ->
        mostRecent = data
    fs.watch fileName, sourceFileReader

  sourceFileWatcher file1
  sourceFileWatcher file2

  getMostRecent = ->
    mostRecent
```

This function can be used like so:

```
mostRecentTweedle = makeMostRecent 'tweedle.dee', 'tweedle.dum'
```

If tweedle.dee has been changed most recently and it contained

```
Contrariwise
```

then invoking the returned function will produce that text:

```
mostRecentTweedle()
# Contrariwise
```

If you try this and see something starting with <Buffer…,then that's okay. The file has just been saved in a different file encoding than the UTF-8 encoding expected by sourceFileWatcher. You can ignore file encodings in this chapter.

The `mostRecent` variable is a *free variable* inside the `getMostRecent` function because it's not defined inside its function but inside the outer `makeMostRecent` function. Directly inside `makeMostRecent`, the `mostRecent` variable is a *bound variable*.