```
fs = require 'fs'
http = require 'http'

makeMostRecent = (file1, file2) ->
  mostRecent = 'Nothing read yet.'

  sourceFileWatcher = (fileName) ->
    sourceFileReader = ->
      fs.readFile fileName, 'utf-8', (error, data) ->
        mostRecent = data
    fs.watch fileName, sourceFileReader

  sourceFileWatcher file1
  sourceFileWatcher file2

  getMostRecent = ->
    mostRecent

makeServer = ->
  mostRecent = makeMostRecent 'file1.txt', 'file2.txt'

  server = http.createServer (request, response) ->
    response.write mostRecent()
    response.end()

  server.listen '8080', '127.0.0.1'

server = makeServer()
```

The earlier makeMostRecent function

Use makeMostRecent inside server

Create server

Using closure, you've been able to isolate two parts of your program and provide a way to get data from one part of a program to another.

3.7. Putting it together

You've looked at functions as discrete parts of a program that use values as arguments, contain expressions, and return values. You've also looked at functions themselves as values and at some of the powerful abstraction techniques that provides. All of this was done in the context of creating a website for Agtron and Scruffy's party. Finally, you have all of the building blocks to create the full solution.

The following listing provides the program to serve a web page with the total number of guests at Scruffy and Agtron's party using the techniques and concepts from this chapter. Note that this listing requires the compiler to be available as a module, so to run it you first need to run `npm`