```
phoneNumbers.hannibal = '555-5525'
phoneNumbers.hannibal
# '555-55525'
```

Suppose you don’t know what properties are in an object. You don’t want to add to or change an object without knowing what properties it has.

Checking for a property name

If you want to check if an object contains a property, use the `of` operator:

```
'hal9000' of phoneNumbers
# true

'skeletor' of phoneNumbers
# false
```

That covers basic object creation and manipulation. In listing 4.2 you see these object features together in a working phone book application. This listing uses some techniques you haven’t seen yet, but those techniques are explained later in this chapter. The program, which runs on Node.js, doesn’t persist changes to the phone book; each time you run it, the phone book will be reset.

Listing 4.2. A simple phone book

```
phonebook =
  numbers:
    hannibal: '555-5551'
    darth: '555-5552'
    hal9000: 'disconnected'
    freddy: '555-5554'
    'T-800': '555-5555'
  list: ->
    "#{name}: #{number}" for name, number of @numbers
  add: (name, number) ->
    if not (name of @numbers)
      @numbers[name] = number
  get: (name) ->
    if name of @numbers
      "#{name}: #{@numbers[name]}"
    else
      "#{name} not found"

console.log "Phonebook. Commands are add get list and exit."
```

The numbers object as a property of phonebook.

The methods of the phonebook object.