```
> add kevin 555-5556
kevin: 555-556
```

Of course, the key-value feature of CoffeeScript objects isn't just for creating phone books.

4.2.2. Key-values for named arguments

Imagine you're purchasing a Maserati (to keep your Ferrari from getting lonely) and that there are different options available to you for customizing it. Suppose that the order process is represented as a single function that passes an argument with your requested color:

```
orderMaserati = (color) ->
  """Order summary
  - Make: Gran Turismo S
  - Color: #{color}
  """
```

Returning formatted output using a whitespace-preserving heredoc

String interpolation into heredoc

The `orderMaserati` function takes a single argument `color` and returns a string using a whitespace-preserving heredoc with the color inserted into the string via *string interpolation* (see section 2.5.2). Scruffy likes metallic black, or *Nero Carbonio* as Maserati calls it, so he orders that:

```
orderMaserati 'Nero Carbonio'
# Order summary:
# - Make: Gran Turismo S
# - Color: Nero Carbonio
```

Maserati lets you customize more than just the color, though. How will the `order` function handle other options?

Multiple arguments

Suppose the interior color is also an option; the function definition gets more complicated:

```
orderMaserati = (exteriorColor, interiorColor) ->
  """Order summary:
  - Make: Gran Turismo
```