What you want to do is add up the existing views. You do that with a comprehension. In this section you'll learn how to use comprehensions to transform the properties and values of an object into other properties and values.

4.3.1. Object comprehensions

You saw previously that comprehensions allow you to deal with the elements of an array without having to write a bunch of boilerplate and iterate manually through every single thing in the array one by one, again and again and again. Here's a refresher in case you forgot:

```
number + 1 for number in [1,2,3,4,5]
# [2,3,4,5,6]
```

Object comprehensions in CoffeeScript work similarly to how array comprehensions work. They have a basic format similar to array comprehensions, except they use the word `of`:

```
expression for property of object
```

What does an object comprehension do? The following listing is a side-by-side comparison with the conceptually equivalent (but not compiled) JavaScript `for...in` loop.

Listing 4.3. Comprehension compared to `for...in` loop

CoffeeScript

```
movie =
  title: 'From Dusk till Dawn'
  released: '1996'
  director: 'Robert Rodriguez'
  writer: 'Quentin Tarantino'


for property of movie
  console.log property
```

JavaScript

```
var movie = {
  title: 'From Dusk till Dawn',
  released: '1996',
  director: 'Robert Rodriguez',
  writer: 'Quentin Tarantino'
}

for (var property in movie) {
  console.log(property);
}
```