```
data =
  X100:
    description: "A really cool camera"
    stock: 5
  X1:
    description: "An awesome camera"
    stock: 6
```

Object describes data

Now, create a new shop by invoking the `constructor` with the data:

```
shop = new Shop data
```

You have two instances of the `Camera` class—both created by the `Shop constructor`. What does this look like in the context of a real program? In listing 5.2 the `Camera` and `Shop` classes are fleshed out to implement the first version of the online shop.

Important: how to run the listings

Listings 5.2, 5.3, 5.4, 5.5, 5.8, 5.10, and 5.11 demonstrate different object-based techniques in CoffeeScript using a small client-side program. The final listing, 5.13, is a small server-side program intended to run each of these different listings. To experiment with the code in the listings, invoke listing 5.13 from the command line with the listing number for the client-side program:

```
> coffee 5.13.coffee 5.2
# => Visit http://localhost:8080/ in your browser
```

Run the server with listing 5.2 as the client script.

Any changes you make to the listings will be automatically reflected in the client script delivered to the browser. So if you make a change to a client-side script and refresh the browser window, you'll see the result of your changes.

In the next listing the `Shop` class fetches raw JSON (see section 4.4.1) from a remote server and uses it to create cameras. The `http` and `get` functions use some browser APIs that you need not be familiar with here. Experiment with the listing to understand how the application fits together.