Listing 5.2. Agtron's camera shop client application (version 1)

```
http = (method, src, callback) ->
  handler = ->
    if @readyState is 4 and @status is 200
      unless @responseText is null
        callback JSON.parse @responseText

  client = new XMLHttpRequest
  client.onreadystatechange = handler
  client.open method, src
  client.send()

get = (src, callback) ->
  http "GET", src, callback

post = (src, callback) ->
  http "POST", src, callback

class Camera
  constructor: (name, info) ->
    @name = name
    @info = info
    @view = document.createElement 'div'
    @view.className = "camera"
    document.body.appendChild @view
    @view.onclick = =>
      @purchase()
    @render()

  render: ->
    @view.innerHTML = "#{@name} (#{@info.stock} stock)"

  purchase: ->
    if @info.stock > 0
      post "/json/purchase/camera/#{@name}", (res) =>
        if res.status is "success"
          @info = res.update
          @render()

class Shop
  constructor: ->
    get '/json/list/camera', (data) ->
      for own name, info of data
        new Camera name, info

shop = new Shop
```

http function for making Ajax requests to the server

get function for making GET Ajax requests to the server

post function for making POST Ajax requests to the server

Camera class with constructor, render method that writes to the web page, and purchase method

Camera class with constructor, render method that writes to the web page, and purchase method

Shop class for initializing the application and creating all the cameras

In the `Camera` and `Shop` classes, this program has clear descriptions for the behavior of products and shops.