```
    <h2>#{@name}</h2>
    <dl class='info'>
    <dt>Stock</dt>
    <dd>#{@info.stock}</dd>
    <dt>Specials?</dt>
    <dd>#{@specials.join(',') || 'No'}</dd>
    </dl>
    """
class Camera extends Product
  category: 'camera'
  megapixels: -> @info.megapixels || "Unknown"
class Skateboard extends Product
  category: 'skateboard'
  length: -> @info.length || "Unknown"
class Shop
  constructor: ->
    unless Product::specials?
      Product::specials = []
    @view = document.createElement 'div'
    @render()
    get '/json/list', (data) ->
      for own category of data
        for own name, info of data[category]
          if info.special?
            Product::specials.push info.special
          switch category
            when 'camera'
              new Camera name, info
            when 'skateboard'
              new Skateboard name, info
  render: ->
    @view.innerHTML = ""
shop = new Shop
```

The Shop constructor dynamically adds a property to the Product prototype.

The Shop constructor also adds all the specials to the specials property of the Product prototype.

At this point it's also informative to show an example of the actual JSON data being used. Here's an example of this JSON.

Listing 5.9. Product listings with specials

```
{
  'camera': {
    'Fuji-X100': {
      'description': 'a camera',
      'stock': 5,
      'arrives': 'December 25, 2012 00:00',
      'megapixels': 12.3
    }
  },
  'skateboard': {
```