```
    'Powell-Peralta': {
      'description': 'a skateboard',
      'stock': 3,
      'arrives': 'December 25, 2012 00:00',
      'length': '23.3 inches'
    }
  }
}
```

Being JSON, the `Shop` constructor is able to easily use this data as an object. Remember, JSON is valid syntax for an object in JavaScript and in CoffeeScript. Inside a CoffeeScript program, the data from listing 5.9 can also be represented with significant indentation:

```
products =
  camera:
    'Fuji-X100':
      description: 'a camera'
      stock: 5
      arrives: 'December 25, 2012 00:00'
      megapixels: 12.3
  skateboard:
    'Powell-Peralta':
      description: 'a skateboard'
      stock: 3
      arrives: 'December 25, 2012 00:00'
         length: '23.3 inches'
```

Through the prototype of a class you're able to modify the properties and behavior of many objects at the same time. This can be done not only with your own classes and objects but also with other objects and classes. Remember, the default for all objects is that they're open to modification. This means you can modify and extend anything, including built-in objects such as the prototypical array.

Objects open by default?

Objects being open means you can change a property on any regular object that you have a reference to. The fifth edition of the ECMAScript standard makes it possible to `freeze` or `seal` an object, preventing it from being modified (see chapter 13).