The stock arrival date is returned in the JSON from the server as a string like this:

```
"October 13, 1975 11:13:00"
```

This is a standard date format that the JavaScript runtime can read.[2] You can create a date from it fairly easily using the built-in `Date` class (otherwise known as the `Date` constructor function):

[2] See IETF RFC 1123 http://tools.ietf.org/html/rfc1123.

```
new Date "October 13, 1975 11:13:00"
```

But Agtron wants it to display how many days from today that is. You think that "how many days from today?" is a question you should be able to ask of any date:

```
productAvailable = new Date "October 13, 1975 11:13:00"
productAvailable.daysFromToday()
```

Because `Date` is a constructor, you have access to the prototype for all the `date` objects. Modify the `Date` prototype and add a `daysFromToday` method:

```
Date::daysFromToday = ->
  millisecondsInDay = 86400000
  today = new Date
  diff = @ - today
  Math.floor diff/millisecondsInDay
```

Travel back in time and imagine that today is January 20, 2012. How many days until Christmas Day 2012?

```
christmas = new Date "December 25, 2012 00:00"
christmas.daysFromToday()
#339
```

December 25, 2012, is in the past, so if you run this example now you will get a negative value.

A warning about dates

Because this executes in a web browser, it will use the time on the user's computer. Potential issues with date in a browser, such as time zones and