```
class Product
  View.include @
  products = []
  @find = (query) ->
    (product for product in products when product.name is query)
  constructor: (@name, @info) ->
    products.push @
    @template = =>
      """
      #{@name}
      """
    @update()
    @handler "onclick", @purchase
  purchase: =>
    if @info.stock > 0
      server.post "/json/purchase/#{@category}/#{@name}", (res) =>
        if res.status is "success"
          @info = res.update
          @update()

class Camera extends Product
  category: 'camera'
  megapixels: -> @info.megapixels || "Unknown"

class Skateboard extends Product
  category: 'skateboard'
  length: -> @info.length || "Unknown"

class Shop
  View.include @
  constructor: ->
    @template = ->
      "<h1>News: #{@breakingNews}</h1>"

    server.get '/json/news', (news) =>
      @breakingNews = news.breaking
      @update()

    server.get '/json/list', (data) ->
      for own category of data
        for own name, info of data[category]
          switch category
            when 'camera'
              new Camera name, info
            when 'skateboard'
              new Skateboard name, info

shop = new Shop
```

The Product class invokes the include class method of View to use it as a mixin.

The Product class still retains the template, which it assigns to new products inside the constructor.

The Shop also uses the View as a mixin.

The Shop also still retains the template. The templates are used by the View mixin.

Finally, in this listing you see the server-side component of the shop.

Listing 5.13. Agtron's shop server application