In the next listing you see a comparison between keeping the state in your program and letting the database keep it. When you run this listing, you'll be able to access one version on http://localhost:9091 and the other on http://localhost:9092. Note that this listing uses an external `db` that's not shown here.

Listing 6.4. State in program or external?

```
http = require 'http'
db = (require './db').stock

stock = 30
serverOne = http.createServer (req, res) ->
  response = switch req.url
    when '/purchase'
      res.writeHead 200, 'Content-Type': 'text/plain;charset=utf8'
      if stock > 0
        stock = stock - 1
        "Purchased! There are #{stock} left."
      else
        'Sorry! no stock left!'
    else
      res.writeHead 404, 'Content-Type': 'text/plain;charset=utf8'
      'Go to /purchase'
  res.end response
```

A server keeping state

```
serverTwo = http.createServer (req, res) ->
  purchase = (callback) ->
    db.decr 'stock', (error, response) ->
      if error
        callback 0
      else
        callback response

  render = (stock) ->
    res.writeHead 200, 'Content-Type': 'text/plain;charset=utf8'
    response = if stock > 0
      "Purchased! There are #{stock} left."
    else
      'Sorry! no stock left'
    res.end response

  switch req.url
    when '/purchase'
      purchase render
    else
      res.writeHead 404, 'Content-Type': 'text/plain;charset=utf8'
      res.end 'Go to /purchase'

serverOne.listen 9091, '127.0.0.1'
serverTwo.listen 9092, '127.0.0.1'
```

A server using a database to keep state