```
      notFound response

numberSold = (salePrice) ->
  50 + 20/10 * (200 - salePrice)

profit = (salePrice, costPrice, overhead) ->
  revenue = (salePrice) ->
    (numberSold salePrice) * salePrice
  cost = (salePrice) ->
    overhead + (numberSold salePrice) * costPrice
  (revenue salePrice) - (cost salePrice)

loadProductData = (makeDbOperator products) 'get'
saveProductData = (makeDbOperator products) 'set'
loadUserData = (makeDbOperator users) 'get'
saveUserData = (makeDbOperator users) 'set'

handleUserRequest = makeRequestHandler loadUserData, saveUserData
handleProductRequest = makeRequestHandler loadProductData,
saveProductData

onProductDataLoaded = (error, data) ->
  price = (parseInt (query.split '=')[1], 10)
  handleProfitRequest
request,response,price,data.costPrice,data.overhead

apiServer = (request, response) ->
  path = url.parse(request.url).path
  query = url.parse(request.url).query
  parts = path.split /\//
  switch parts[1]
    when 'user'
      handleUserRequest request, response, parts[2]
    when 'product'if parts.length == 4 and /^profit/.test parts[3]

        loadProductData parts[2], onProductDataLoaded
      else
        handleProductRequest request, response, parts[2]
    else
      notFound response

server = http.createServer(apiServer).listen 8080, '127.0.0.1'

exports.server = server
```

In terms of the total number of lines, this program is no shorter; it would be possible to make it substantially shorter with different abstractions, but in