this case communicating the intention of every part of the program is preferred to brevity. Choose techniques appropriate for your circumstances.

Abstraction isn't always about extracting common code. Sometimes you need to change multiple things in a program at once. Instead of writing it in three places when you obviously don't need to, you can start with the abstraction.

6.3.2. Adding common code

Imagine Scruffy calls you at 2:00 a.m. to inform you that the server for Agtron's online store was running so hot that it burst into flames. Sure, nothing that dramatic really happens to you, but consider that your server is having problems because it's using too much processing power, and you learn that the culprit is the database. Your program is making too many requests to the database, so you need to reduce the number of requests it receives. Here are the last 10 lines from the database log:

```
request GET 'All work and no play'
response 'makes Jack a dull boy' (5 ms)
request GET 'All work and no play'
response 'makes Jack a dull boy' (4 ms)
request GET 'All work and no play'
response 'makes Jack a dull boy' (2 ms)
request GET 'All work and no play'
response 'makes Jack a dull boy' (5 ms)
request GET 'All work and no play'
response 'makes Jack a dull boy' (5 ms)
```

That's right; your program is constantly asking the database to fetch the same value. You might imagine that a clever database would cache the responses for you. You might imagine that, but all the while the server is on fire. What can you do?

Specific cache

You recognize that by caching the previous response you can avoid making another request to the database if you need the same value twice in a row. It's tempting to just add caching to the `makeDbOperator` function, but where do you add it?