ranked in an array, top team first:

```
teams = ['wolverines', 'sabertooths', 'mongooses']
```

You want to pass the first item (called the *head* of the array) as one parameter and the remaining items (called the *tail*) as the remaining parameters. Doing that manually is clumsy:

```
highlight teams[0], teams[1], teams[2]
```

Your fingers would be sore from typing after a hundred team names or so. The alternative is to *spread* the teams in the array across the function parameters:

```
highlight teams...
```

Compare two different invocations of the `highlight` function:

```
highlight teams
highlight teams...
```

highlight is invoked with the teams array as the first argument.

highlight is invoked with the teams array spread across as many arguments as there are items in the array.

Suppose now that you have an `insert` function that takes a spread, and you want to invoke it from within another function that also takes a spread. Passing the name of the rest parameters directly to `insert` doesn't work:

```
insert = (teams...) ->
  teams

initialize = (teams...) ->
  insert teams

initialize 'wolverines', 'sabertooths', 'mongooses'
# [ [ 'wolverines','sabertooths', 'mongooses' ] ]
```

For demonstration, this insert function simply returns the names parameter.

Invoke insert with the name of the rest parameter.

The rest parameter for `insert` ends up as an array wrapped in an array—definitely not what you wanted. But using the spread you can get the result you need: