```
class Smtp
  constructor: ->
  connect: (host, port=25) ->
  send: (message, callback) ->
```

Would you expect users to adopt this interface?

```
smtp = new Smtp
smtp.connect 'coffeescriptinaction.com'
smtp.send 'MAIL FROM: scruffy@coffeescriptinaction.com', (response)
->
  if response.contains 'OK'
    smtp.send 'RCPT TO: agtron@coffeescriptinaction.com',
(response) ->
```

What's the problem with that? For one thing, it looks worse than the raw SMTP. The users of your API don't even care how SMTP works or indeed whether their email is delivered using SMTP at all. Worse, you're forcing users to either flatten your API calls themselves or live in nested callback hell. Not good, but what can you do instead?

Have some empathy and approach the problem as a user. How should it look? How do *you* want to define and send an email?

```
scruffysEmail = new Email
  to: ''
  from: ''
  body: '''

  '''

scruffysEmail.send()
```

This is simpler. Notice how any mention of SMTP is absent? A user doesn't care about how SMTP works; they just want to send an email. It's up to the mail library to determine how to connect to SMTP. Instead of copying the format of the protocol, copy the format that makes sense to people who use your library. Write the program in the language of the user.

The next listing shows this technique in action. This listing requires a dependency called simplesmtp, so if you intend to run it directly, you should first install the dependency: