```
> npm install simplesmtp
```

Once the dependency is installed, you can run the listing.

Listing 8.2. An object literal–based DSL for email (email.coffee)

```
simplesmtp = require 'simplesmtp'

class Email
  SMTP_PORT = 25
  SMTP_SERVER = 'coffeescriptinaction.com'
  constructor: ({@to, @from, @subject, @body}) ->
  send: ->
    @client = simplesmtp.connect SMTP_PORT, SMTP_SERVER
    @client.once 'idle', ->
      @client.useEnvelope
        from: @from
        to: @to

    @client.on 'message', ->
      client.write """
      From: #{@from}
      To: #{@to}
      Subject: #{@subject}

      #{@body}

      """
      client.end()
```

A library called simplesmtp is used to handle SMTP details.

Class variables (chapter 5).

Shorthand constructor (chapter 5).

The send method uses simplesmtp to connect, wait until the connection is ready, and then send the message.

Using the library provided by listing 8.2 doesn't require the user to know SMTP:

```
scruffysEmail = new Email
  to: 'agtron@coffeescriptinaction.com'
  from: 'scruffy@coffeescriptinaction.com'
  subject: 'Hi Agtron!'
  body: '''

  This is a test email.

  '''

scruffysEmail.send()
# { to: 'agtron@coffeescriptinaction.com',
#   from: 'scruffy@coffeescriptinaction.com',
#   subject: 'Hi Agtron!',
#   body: '\nThis is a test email. \n
# Error: connect ETIMEDOUT
```

Invoke the constructor with an object literal representing the email to send.

' }

There is no SMTP server on the domain coffeescriptinaction.com, so this request will fail.