```
fs = require 'fs'
coffee = require 'coffee-script'

evalScruffyCoffeeFile = (fileName) ->
  fs.readFile fileName, 'utf-8', (error, scruffyCode) ->
    letReplacedScruffyCode = scruffyCode.replace /\slet\s/, ' $LET ' <-- Replace let keyword with the string $LET.
    return if error
    tokens = coffee.tokens letReplacedScruffyCode

    i = 0
    consumingLet = false
    waitingForOutdent = false
    while token = tokens[i]
      if token[0] is 'IDENTIFIER' and token[1] is '$LET'
        consumingLet = true
        doToken = ['UNARY', 'do', spaced: true]
        tokens.splice i, 1, doToken
      else if consumingLet
        if token[0] is 'CALL_START'
          paramStartToken = ['PARAM_START', '(', spaced: true]
          tokens[i + 1][2] = 0
          tokens.splice i, 1, paramStartToken
        if token[0] is 'CALL_END'
          paramEndToken = ['PARAM_END', ')', spaced: true]

          functionArrowToken = ['->', '->', spaced: true]
          indentToken = ['INDENT', 2, generated: true]
          tokens.splice i, 2, paramEndToken, functionArrowToken, indentToken
          consumingLet = false
          waitingForOutdent = true
      else if waitingForOutdent
        if token[0] is 'OUTDENT' or token[0] is 'TERMINATOR'
          outdentToken = ['OUTDENT', 2, generated: true]
          tokens.splice i, 0, outdentToken
          waitingForOutdent = false
      i++

    nodes = coffee.nodes tokens

    javaScript = nodes.compile()
    eval javaScript

fileName = process.argv[2]
process.exit 'No file specified' unless fileName
    evalScruffyCoffeeFile fileName
```

If there is a $LET in the token stream, convert it to a do.

The let variables are passed in as parameters to the do.

The body of the do is indented.

The next unbalanced outdent must indicate the end of the current block. That's where the do must also be outdented.

As before, modifying the token stream is possible, but it can be risky and is definitely not for the faint of heart. Scruffy achieved his implementation of `let` by rewriting source before tokenization and by rewriting the token stream, but it would also be possible to manipulate the AST instead of using a token rewriter. It's *your* language, so for your circumstances it might make sense to completely change the syntax. You own the language.

8.5. Summary