9.4.1. Lazy data handling

The data that you have now and the data that you'll have as the result of a series of events isn't as different as you might think. In a sense, the difference is that an array is an expression of the value:

```
['Geralyn Turnbull', 'Connie Renyer']
```

Whereas the data that you don't have yet is like a function that returns the data:

```
-> ['Geralyn Turnbull', 'Connie Renyer']
```

The first expression is the data itself; the second returns the data when invoked. This makes a good starting place on the road to composing asynchronous events.

Imagine that you need to do more with the list of names than just display them; imagine that you want to put them into a phone book like the one from chapter 4:

```
phoneNumbers = [
  { name: 'hannibal', number: '555-5551', relationship: 'friend' }
  { name: 'darth', number: '555-5552', relationship: 'colleague' }
  { name: 'hal_9000', number: 'disconnected', relationship:
'friend' }
  { name: 'freddy', number: '555-5554', relationship: 'friend' }
  { name: 'T-800', number: '555-5555', relationship: 'colleague' }
]
```

To get an array containing only friends, you either use a comprehension with a `when` clause or the `Array::filter` method. In this case, use `filter`:

```
relationshipIs = (relationship) ->
 (item) -> item.relationship is relationship

phoneNumbers
.filter(relationshipIs 'friend')
```