The script referenced by `<script src='status.js'></script>` is a JavaScript file, but your browser-based program will be written in CoffeeScript. How do you deliver your CoffeeScript program to a browser?

11.1.1. Manual compilation

The first option you have is to use the manual command-line CoffeeScript compiler. But that will quickly become tedious if you have to invoke the compiler every time you change your program. Suppose the program is contained in the file status.coffee:

```
> coffee –c status.coffee
```

You don’t want to manually recompile again and again. There are other options; one of them is to send CoffeeScript straight to the browser.

11.1.2. Browser compilation

Browsers execute JavaScript, not CoffeeScript. But because CoffeeScript is implemented *in CoffeeScript*, a compiled version of CoffeeScript can run in the browser and compile CoffeeScript for you on the fly. Read the previous sentence again. Let it sink in.

Once you’re ready, you can compile CoffeeScript in a browser by first including a browser-specific version of CoffeeScript:

```
<script src='http://coffeescript.org/extras/coffee-script.js'>
</script>
```

Once your HTML document has that, you can include a CoffeeScript source file:

```
<script type='text/coffeescript' src='status.coffee'></script>
```

Web browsers don’t recognize the `text/coffeescript` script *type*, but by including CoffeeScript in the browser, the CoffeeScript compiler can turn your CoffeeScript source files into JavaScript on the fly. How does it