```
framesPerSecond = (n) ->
  (seconds 1)/n

makeUpdater = (buffer = []) ->
  bufferRenderer = (json) ->
    buffer.push (JSON.parse json).hits
    render buffer

  ->
    window.setInterval ->
      fetch '/feed.json', bufferRenderer
    , framesPerSecond 20

updater = makeUpdater()
updater()
```

This makeUpdater function returns a function that will, in turn, return a function that creates an updater.

A Request to feed.json returns JSON containing the number of hits.

But as with most things in browser-based programs, there's a catch. Although some code (such as JSON data for Agtron's servers) is safe to hot load,

```
{
  'servers': [
    {
      'name': 'tolimas'
      'cpu': 22,
      'network': {
        'in': 2343,
        'out' 3344
      }
    }
  ]
}
```

other code can be unsafe, and unsafe code (be it malicious or clumsy) inserted into a hot program can have disastrous effects. Imagine dynamically inserting a script that overrides the built-in `map` method (chapter 5) on the `Array` prototype. All of your arrays will break!

```
Array::map = -> null

[9,8,7,6].map (item) -> item*2
# null
```

Suppose this line is hot-loaded.

Any use of map will now return null.

If you load source code into your program, there's a chance that source code will do something that you don't want it to. It's possible to sandbox code in a browser as you learned to do on the server (in chapter 8), but the