

Job done, right? Not quite. Agtron later informs you that your polyfill doesn't implement the entire specification (you know, the one you didn't have time to read). There's actually a second parameter (see chapter 13). To prevent people from getting nasty surprises when they use your polyfill, you take the approach of throwing an exception if the polyfill is used for part of the specification that it doesn't implement:

```
Object.create ?= (prototype, extensions) ->
  if extensions
    throw new Error 'Not supported by this implementation'
  else
    F = ->
    F.prototype = prototype
    new F()
```

Throw an exception if this method is invoked with a second parameter.

Not all language features can be fixed with a polyfill in this way. Any language feature that requires syntax can't be polyfilled at runtime. Writing a polyfill for language syntax would be like building a house out of wallpaper. Changing syntax means compilation. Back to Agtron's dashboard—how will you create those graphs that Agtron wants? More generally, how will you create the user interface?

11.4. Creating a user interface

There are two styles of managing your drawing in a web browser: *retained mode* and *immediate mode*. Although web browsers have traditionally used a retained mode, some recent APIs such as `canvas` are immediate mode. The difference between retained and immediate mode isn't crucial to your understanding of CoffeeScript, but understanding it will help you write better CoffeeScript programs in the browser. It's time to learn both.

11.4.1. Retained mode with the DOM