```
fetch = (src, callback) ->
  head = document.querySelector 'head'
  script = document.createElement 'script'
  ajaxCallbackName = nextCallbackName()
  window[ajaxCallbackName] = (data) ->
    callback data
  script.src = src + "?callback=#{ajaxCallbackName}"
  head.appendChild script

seconds = (n) ->
  1000*n

framesPerSecond = (n) ->
  (seconds 1)/n

makeUpdater = (buffer = []) ->
  bufferRenderer = (json) ->
    buffer.push (JSON.parse json).hits
    if buffer.length is 22 then buffer.shift()
    render buffer

  ->
    window.setInterval ->
      fetch '/feed.json', bufferRenderer
    , framesPerSecond 1

updater = makeUpdater()
updater()
```

A request to feed.json returns JSON containing the number of hits.

Agtron wants a line chart. How do you draw a line chart? Drawing a line chart using regular DOM elements wouldn't be much fun, so instead you'll draw the line chart using something called *canvas* that involves immediate-mode techniques.

11.4.2. Immediate mode with HTML5 canvas

In immediate mode, the view is only a buffer, and what you draw to it has no life outside of that buffer. There's no way to get elements back out of the buffer, so you never directly access or manipulate them. The HTML5 feature called *canvas* provides an immediate-mode API for browser-based drawing.

For now, assume that the standard `canvas` interface is supported everywhere you need it to be—if it isn't, you can write a polyfill for it later. To create a canvas, you create a new `canvas` element, append it to the