```
render = (buffer) ->
  drawGraph buffer
  drawTitle 'Server Dashboard'

nextCallbackId = do ->
  callbackId = 0
  -> callbackId = callbackId + 1

nextCallbackName = ->
  "callback#{nextCallbackId()}"

fetch = (src, callback) ->
  head = document.querySelector 'head'
  script = document.createElement 'script'
  ajaxCallbackName = nextCallbackName()
  window[ajaxCallbackName] = (data) ->
    callback data
  script.src = src + "?callback=#{ajaxCallbackName}"
  head.appendChild script

seconds = (n) ->
  1000*n

framesPerSecond = (n) ->
  (seconds 1)/n

makeUpdater = (buffer = []) ->
  bufferRenderer = (json) ->
    buffer.push (JSON.parse json).hits
    if buffer.length is 22 then buffer.shift()
    render buffer

  ->
    window.setInterval ->
      fetch '/feed.json', bufferRenderer
    , framesPerSecond 1

updater = makeUpdater()
updater()
```

The programs in listings 11.4 and 11.5 both update several times per second. The constantly changing data makes the graphs look like they're moving. This movement is stuttered, but the feeling of movement is there nonetheless.

Animation can be a subtle and nuanced thing, but the realization that you don't need to explicitly request animation to make something appear