```
task 'test' , 'run the tests', ->
  clean 'compiled', ->
    compile 'app', ->
      compile 'spec', ->
        runSpecs 'compiled', ->
          console.log 'Tests complete'

task "development:start", "start on development", ->
  runApp 'development'

SERVER = require('./app/config').production.host

deploy = ->
  console.log "Deploy..."
  tarOptions = ["-cvf","artifact.#{VERSION}.tar","compiled"]
  execFile "tar", tarOptions,(err, data) ->
    console.log '1. Created artifact'
    execFile 'scp', [
      "artifact.#{VERSION}.tar",
      "#{SERVER}:~/."
    ], (err, data) ->
      console.log '2. Uploaded artifact'
      exec """
      ssh #{SERVER} 'cd ~/;
      rm -rf compiled;
      tar -xvf artifact.#{VERSION}.tar;
      cd ~/compiled;
      NODE_ENV=production nohup node app/server.js &' &
      """, (err, data) ->
        console.log '3. Started server'
        console.log 'Done'

task "production:deploy", "deploys the app to production", ->
  clean 'compiled', ->
    compile 'app', ->
      copy 'content', 'compiled', ->
        createArtifact 'compiled', VERSION, ->
          deploy()
```

A test run requires a build but not an artifact.

Starting on development simply executes Node.

A sample config file is provided in the downloadable code.

Details of the SSH command used are omitted here for brevity.

The Cakefile in listing 12.19 would have been large and difficult to read if all of the functions called from the build tasks were included. Instead, those functions are in another file called build_utilities.coffee, which appears in the following listing.

Listing 12.20. Build utilities (build_utilities.coffee)