```
fs = require 'fs'
{spawn, exec, execFile, fork} = require 'child_process'

clientCompiled = false

forAllSpecsIn = (dir, fn) ->
  execFile 'find', [ dir ], (err, stdout, stderr) ->
    fileList = stdout.split '\n'
    for file in fileList
      fn file if /_spec.js$/.test file

compileClient = (callback) ->
  return callback() if clientCompiled
  clientCompiled = true
  compiler = require 'coffee-script'
  modules = fs.readFileSync "lib/modules.coffee", "utf-8"
  modules = compiler.compile modules, bare: true
  files = fs.readdirSync 'client'
  fs.mkdirSync "compiled/app/client"
  source = (for file in files when /\.coffee$/.test file
    module = file.replace /\.coffee/, ''
    fileSource = fs.readFileSync "client/#{file}", "utf-8"
    fs.writeFileSync "compiled/app/client/#{module}.js",
        compiler.compile fileSource
    """
    defmodule({#{module}: function (require, exports) {
      #{compiler.compile(fileSource, bare: true)}
    }});
    """
  ).join '\n\n'

  out = modules + '\n\n' + source
  fs.writeFileSync 'compiled/app/client/application.js', out

  callback?()
```

The Node.js module for external processes is required.

Look at a directory of files and execFile each one.

Compile the client-side modules to work on the client and concatenate them.

Compile the client-side modules to work on the client and concatenate them.