```
new Formulaic document, '#contact-details'
```

Agtron tells you that extending and improving Formulaic will require you to learn some ECMAScript 5 *and* some ECMAScript 6 features. Sounds good! Time to get started.

13.1.2. Future JavaScript features that CoffeeScript has today

Some of the features coming in future versions of ECMAScript are already present in CoffeeScript in one form or another. This means that even if the names of these features sound only vaguely familiar, you already know and use `rest` and `spread` parameters, template strings, default parameters, and destructuring assignment. Because you already know them, it's best to get them out of the way before moving on to the interesting stuff.

rest and spread

The `rest` and `spread` operators proposed for ECMAScript 6 work the same way as the ones you're familiar with in CoffeeScript (aside from some syntactical differences). Here's the CoffeeScript syntax you're familiar with:

```
rest = (a, b, r...) -> r
rest 1,2,3,4,5,6,7
# [3,4,5,6,7]

spread = [1,2,3,4,5,6,7]
rest spread
# [3,4,5,6,7]
```

In JavaScript with ECMAScript 6 it looks similar, but the ellipsis goes on the front of the variable name:

```
rest = function (a, b, ...r) {  return r; }
rest(1,2,3,4,5,6,7);
# [3,4,5,6,7]
```

ECMAScript 6 example

The ECMAScript 6 specification also has string interpolation.

Template strings